

L310 Three Piece Full Port Ball Valve

Size Range 1/4" - 4" (DN08 - DN100)

Pressure Rating DIN PN63


Materials Stainless Steel, Carbon Steel

End Connection Threaded, Butt weld,
Socket weld and others

Service Application Water, Oil, Gas, Thermal Fluid,
Chemicals and others

Certifications ISO 9001, PED 97/23/EC

Operation Manual



MATERIAL LIST:

ITEM	DESCRIPTION	STAINLESS STEEL	CARBON STEEL	Q'TY
1	BODY CAP	ASTM A351 CF8M	ASTM A216 WCB	2
2	BALL	ASTM A351 CF8M/316	ASTM A216 CF8/304	1
3	SEAT	PTFE	PTFE	2
4	BODY GASKET	PTFE	PTFE	2
5	BODY	ASTM A351 CF8M	ASTM A216 WCB	1
6	TRUST WASHER	PTFE	PTFE	1
7	STEM PACKING	PTFE	PTFE	1-2
8	GLAND	AISI 304	AISI 304	1
9	STEM	ASTM A276 316	ASTM A276 304	1
10	SPRING WASHER	AISI 304	AISI 304	1
11	HANDLE NUT	AISI 304	AISI 304	1
12	BODY BOLT	AISI 304	CARBON STEEL	4-6
13	BOLT WASHER	AISI 304	CARBON STEEL	4-6
14	BODY NUT	AISI 304	CARBON STEEL	4-6
15	HANDLE	AISI 304	ZINC PLATED STEEL	1
16	SLEEVE	VINYL PLASTISOL	VINYL PLASTISOL	1

DIMENSIONS:

SIZE		ØD		L		H		W		ØA		B		Weights KG
IN	DN	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM	
1/4"	8	0.43	11.0	1.97	50.0	2.20	56.0	3.54	90.0	0.56	14.2	0.39	10.0	0.4
3/8"	10	0.49	12.5	2.36	60.0	2.20	56.0	3.54	90.0	0.69	17.6	0.39	10.0	0.4
1/2"	15	0.59	15.0	2.95	75.0	2.40	61.0	3.94	100.0	0.86	21.8	0.51	13.0	0.6
3/4"	20	0.79	20.0	3.15	80.0	2.52	64.0	3.94	100.0	1.07	27.2	0.51	13.0	0.7
1"	25	1.00	25.4	3.54	90.0	2.87	73.0	5.31	135.0	1.33	33.9	0.59	15.0	1.0
1 1/4"	32	1.26	32.0	4.33	110.0	3.07	78.0	5.31	135.0	1.68	42.7	0.59	15.0	1.2
1 1/2"	40	1.50	38.0	4.72	120.0	3.43	87.0	6.69	170.0	1.92	48.8	0.63	16.0	2.4
2"	50	1.97	50.0	5.51	140.0	3.78	96.0	6.69	170.0	2.41	61.2	0.63	16.0	3.3
2 1/2"	65	2.56	65.0	7.28	185.0	5.71	145.0	10.24	260.0	2.91	73.9	0.67	17.0	7.6
3"	80	3.15	80.0	8.07	205.0	6.10	155.0	10.24	260.0	3.54	89.8	0.67	17.0	12.0
4"	100	3.94	100.0	9.45	240.0	7.13	181.0	11.02	280.0	4.54	115.3	0.79	20.0	21.0

P-T RATINGS

